

0879158-061301
T06T90-09T490

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29

**MULTI-RESOLUTION BOUNDARY ENCODING APPLIED
TO REGION BASED STILL IMAGE AND VIDEO ENCODING**

Technical Field

The present invention relates to still image and video encoding, and, in particular, to region based still image and video encoding.

Background

Video encoding may include image encoding and boundary encoding. Existing boundary encoding techniques, such as MPEG-4, typically use differential chain codes for generating region based encoding. An examples of differential chain encoding is described in Muller, et. al., "Progressive Transmission of Line Drawings Using the Wavelet Transform," IEEE Transactions On Image Processing, Vol. 5, No. 4, April 1996. Differential chain encoding techniques typically use directional vectors on a square grid of for example, 4x4 pixels.

However, MPEG-4 and other differential chain encoding techniques only code the pixel boundaries of the regions, and thus may not have an overall multi-resolution representation. As a result, if some information is lost in transmission, the boundary of the whole region may be misplaced.

Fourier series based encoding is the next step in boundary encoding, with coordinates of a curve periodically extended and Fourier transformed. However, Fourier series encoding only generates good localization in frequency, but not good localization in space. Accordingly, once there is error in transmission, i.e., some of the coefficients or data bits are lost, the boundary may be misplaced.

Summary

A method for applying multi-resolution boundary encoding to region based still image and video encoding includes dividing an original image into a plurality of regions and detecting a plurality of boundaries associated with the plurality of the regions. The method further includes encoding each of the plurality of the boundaries so that each of the plurality of the boundaries contains different resolution coefficients. The method also includes decomposing each of the plurality of the regions in the original image into one or more subbands using the plurality of the boundaries with the highest resolution coefficients, and successively decomposing each of the plurality of the regions

09879158-061301
FOET90-9T62860

1 in a subband with lower resolution coefficients into one or more subbands using the plurality of the
2 boundaries with lower resolution coefficients.

3 The method for applying multi-resolution boundary encoding to region based still image and
4 video encoding further includes transmitting the lowest resolution boundary and image information,
5 and successively transmitting higher resolution boundary and image information.

6 This method uses multi-resolution encoding for image and for boundary and allows for
7 better error correction for low frequency transmission. By using joint source channel coding
8 (JSCC) techniques, a receiver with low resolution capability or low channel bandwidth may still
9 render a close approximation of a boundary despite error in transmission.

10 **Description of the Drawings**

11 The preferred embodiments of the multi-resolution encoding will be described in detail with
12 reference to the following figures, in which like numerals refer to like elements, and wherein:

13 Figure 1 illustrates exemplary hardware components of a computer that may be used to
14 implement the multi-resolution boundary encoding;

15 Figure 2 illustrates an exemplary boundary encoded at full resolution;

16 Figures 3(a) and 3(b) illustrate an exemplary method for encoding two one-dimensional
17 periodical signals using wavelet based encoding at different resolution levels;

18 Figures 4(a)-(c) illustrates how the exemplary boundary shown in Figure 2 is represented
19 in multi-resolution encoding;

20 Figure 5(a) illustrates an exemplary multi-resolution representation for boundaries;

21 Figure 5(b) illustrates an exemplary comparison of Fourier series encoding and wavelet
22 based encoding with or without transmission errors;

23 Figures 6(a)-(c) illustrate an exemplary image encoding using subband encoding technique;

24 Figures 7(a)-(d) illustrate an exemplary multi-resolution decomposition of an image and an
25 associated boundary;

26 Figures 8(a)-(e) illustrate an exemplary process of progressive reconstruction of the image
27 and the associated boundary; and

28 Figure 9 is a flow chart of the exemplary decomposition and reconstruction process
29 illustrated in Figures 7 and 8 using multi-resolution boundary encoding.

30

09379158-051304
FOI b7 - b7C - b7E

1 **Detailed Description**

2 A method and an associated apparatus applies multi-resolution boundary encoding to
3 region based still image and video encoding, allowing better error correction for low frequency
4 bands. High frequency bands may be less protected, leaving only lower frequency representation
5 highly protected. A receiver with low resolution capability or low channel bandwidth, such as a
6 wireless device, may still render a close approximation of a boundary despite error in transmission.

7 Figure 1 illustrates exemplary hardware components of a computer 100 that may be used
8 to implement the multi-resolution boundary encoding. The computer 100 includes a connection
9 with a network 118 such as the Internet or other type of computer or telephone networks. The
10 computer 100 typically includes a memory 102, a secondary storage device 112, a processor 114,
11 an input device 116, a display device 110, and an output device 108.

12 The memory 102 may include random access memory (RAM) or similar types of memory.
13 The memory 102 may be connected to the network 118 by a web browser 106. The web
14 browser 106 makes a connection via the world wide web (WWW) to other computers known as
15 web servers, and receives information from the web servers that are displayed on the computer
16 100. The secondary storage device 112 may include a hard disk drive, floppy disk drive, CD-
17 ROM drive, or other types of non-volatile data storage, and may correspond with various
18 databases or other resources. The processor 114 may execute information stored in the memory
19 102, the secondary storage 112, or received from the Internet or other network 118. The input
20 device 116 may include any device for entering data into the computer 100, such as a keyboard,
21 key pad, cursor-control device, touch-screen (possibly with a stylus), microphone, or video camera
22 (not shown). The display device 110 may include any type of device for presenting visual image,
23 such as, for example, a computer monitor, flat-screen display, or display panel. The output device
24 108 may include any type of device for presenting data in hard copy format, such as a printer (not
25 shown), and other types of output devices include speakers or any device for providing data in
26 audio form. The computer 100 can possibly include multiple input devices, output devices, and
27 display devices.

28 Although the computer 100 is depicted with various components, one skilled in the art will
29 appreciate that the computer can contain additional or different components. In addition, although
30 aspects of an implementation are described as being stored in memory, one skilled in the art will

05579155-051301
10579155-051301

1 appreciate that these aspects can also be stored on or read from other types of computer program
2 products or computer-readable media, such as secondary storage devices, including hard disks,
3 floppy disks, or CD-ROM; a carrier wave from the Internet or other network; or other forms of
4 RAM or ROM. The computer-readable media may include instructions for controlling the
5 computer 100 to perform a particular method.

6 Any signal can be represented with scaling functions and wavelet functions. The scaling
7 functions, wavelet functions, and other image encoding related mathematical formulas and
8 algorithms are described, for example, in Chuang, et. al., "Wavelet Descriptor of Planar Curves:
9 Theory and Applications," IEEE Transactions on Image Processing, Vol. 5, No. 1, January 1996,
10 which is incorporated herein by reference. Chuang, et. al. describe a hierarchical planar curve
11 descriptor that, by using a wavelet transform, decomposes a curve into components of different
12 scales so that the coarsest scale components carry the global approximation information while the
13 finer scale components contain the local detailed information. The wavelet descriptor is shown to
14 have many desirable properties such as multi-resolution representation, invariance, uniqueness,
15 stability, and spatial localization.

16 Multi-resolution pyramid encoding for image is described, for example, in United Patent
17 No. 5,477,272, entitled "Variable-Block Size Multi-Resolution Motion Estimation Scheme for
18 Pyramid Coding," which is incorporated herein by reference. U.S. Patent No. 5,477,272
19 describes a variable-size block multi-resolution motion estimation scheme that can be used to
20 estimate motion vectors in subband encoding, wavelet encoding and other pyramid encoding
21 systems for video compression.

22 In multi-resolution encoding, image information is sent in increments. Every time more
23 information is transmitted, the image may be better described and rendered. For example, a single
24 sine wave may be a first approximation of a square wave, which represents an original waveform.
25 Adding more information, for example, a double frequency sine wave with different amplitude, on
26 top of the original sine wave may generate a second approximation of the square wave. A third
27 approximation may be generated by adding a higher frequency sine wave with smaller amplitude,
28 and so on. Every time a new sine wave is added, a better approximation of the square wave, the
29 original image, may be generated.

09876543210
9876543210
9876543210

1 Multi-resolution encoding techniques may be applied to boundary encoding. In multi-
2 resolution boundary encoding, a periodic wave transfer may be generated with different contents
3 of frequencies. Figure 2 illustrates an exemplary boundary B-V₀ 330 encoded at full resolution.
4 The boundary is composed of two coordinates, i.e., $x(t)$ and $y(t)$, that evolve in “ t ”. The
5 combination of the two coordinates generates the whole boundary.

6 The boundary may be encoded using two one-dimensional periodic wavelet series.
7 Wavelet series are described, for example, in “Progressive Transmission of Line Drawings Using
8 the Wavelet Transform” by Muller, et. al., IEEE Transactions on Image Processing, Vol. 5, No.
9 4, April 1996, which is incorporated herein by reference. Muller, et. al. present a method to apply
10 progressive transmission to line drawings using wavelet transform.

11 Figures 3(a) and 3(b) illustrate an exemplary method for encoding, i.e., decomposing, two
12 one-dimensional periodical signals using wavelet based encoding at different resolution levels.
13 Examples of one-dimensional periodical signal encoding are described, for example, in “Wavelets
14 and Subband Coding” by Vetterli and Kovacevic, ISBN 0-13-097080-8, 1995, 221-223, which
15 is incorporated herein by reference.

16 Referring to Figure 3(a), a one-dimensional curve $X(w)$ is decomposed by subdividing the
17 spectrum represented by frequency “ w ” and generating frequency coefficients for $x(t)$. For
18 example, wavelet coefficients in B-V₀ 330 expand all frequency bands from 0 to π . Subdividing
19 the spectrum generates coefficients in B-V₁ 430, which contains lower frequencies from $0-\pi/2$, and
20 B-W₁ 440, which contains higher frequencies from $\pi/2$ to π . Further dividing the spectrum
21 produces coefficients in B-V₂ 530, which carries lower frequency contents from $0-\pi/4$, and B-W₂
22 540, which carries higher frequency contents from $\pi/4$ to $\pi/2$. Yet further dividing the spectrum
23 produces coefficients in B-V₃ 630, which contains lower frequency contents from $0-\pi/8$, and B-
24 W₃ 640, which carries higher frequency contents from $\pi/8$ to $\pi/4$.

25 Figures 4(a)-(c) illustrates how the exemplary boundary shown in Figure 2 is represented
26 in multi-resolution encoding. First, a few data bits with lowest frequency coefficients, which
27 represent the most basic boundary information, are sent to a receiver during transmission. Then,
28 more data bits with higher frequency coefficients may be sent to render a better approximation of
29 the boundary. The more data bits with higher frequency coefficients are transmitted, the closer
30 representation the boundary is to the original image.

09879158.051301

1 As shown in Figure 4(a), $X(w)$ and $Y(w)$, which form the transformed boundary, may be
2 reconstructed by first receiving $B-V_2 530$, which contains the lowest frequency contents. Then,
3 $B-W_2 540$, which carries mid-range frequency contents, may be received, thereby creating a better
4 boundary. $B-V_1 430$, shown in Figure 4(b), may be generated by combining $B-V_2 530$ and $B-W_2$
5 540 . Lastly, $B-W_1 440$, which contains the highest frequency contents, may be received, and $B-V_0$
6 330 , the original boundary shown in Figure 4(c), may be generated by combining $B-V_1 430$ and
7 $B-W_1 440$. As a result, $B-V_0 330$ is the combination of $B-V_2 530$, $B-W_2 540$ and $B-W_1 440$.

8 Figure 5(a) illustrates an exemplary multi-resolution representation for boundaries. An
9 image, such as a snowflake, may be transmitted by sending frequency coefficients in increments.
10 The original image with the highest frequency coefficients is shown in (0). The image with the
11 lowest frequency coefficients, i.e., the basic shape, is shown in (8). If a receiver has higher
12 transmission capability, higher frequency coefficients may be added to generate the image shown
13 in (7), and so on. As illustrated in multi-resolution wavelet based boundary encoding, each time
14 more information is received, the image boundary may be enhanced slightly with higher resolution,
15 i.e., more detail. As for the final layers of transmission shown, for example, in (3), (2), (1), the
16 enhancements generated may not be perceivable by human visual system, and the coefficients that
17 generate (3), (2), (1) do not need to be protected against channel errors. Accordingly, high
18 frequency bands may be discarded, leaving only lower frequency representation. Multi-resolution
19 boundary encoding enables the basic shape of boundaries to be preserved by transmitting only a
20 few coefficients.

21 Multi-resolution wavelet based boundary encoding offers a better approach than chain
22 codes or Fourier series encoding, where if one data bit in the chain code is missing, the whole
23 boundary is misplaced. Figure 5(b) illustrates an exemplary comparison of Fourier series encoding
24 and wavelet based encoding. Fourier series based encoding uses sine and cosine infinite
25 waveforms, thus there is no spatial representation. If the frequency of the infinite waveform is
26 changed slightly, the overall appearance of the image and boundary may be changed. The wavelet
27 transform, however, has good localization both in space and in frequency.

28 The original waveform is shown in (a). Changing one coefficient slightly in the Fourier
29 series encoding generates (b), while changing the similar coefficients slightly in wavelet based
30 encoding generates (c) and (d). As illustrated, in Fourier series encoding, an error in transmission,

1 represented by a slight change in one coefficient, disturbs the entire boundary. On the other hand,
 2 in wavelet based encoding, a similar error results in localized movement of the boundary.
 3 Therefore, if errors exist in the transmission, a receiver is still able to recover the basic coefficients
 4 and render a close approximation of the boundary.

5 The advantage of localization of modification may be shown best in wireless image
 6 transmission, where noisy channels are used and errors frequently occur. An error in transmission
 7 may affect one or more of the coefficients, typically the high frequency coefficients because the high
 8 frequency coefficients are not as protected as the low frequency coefficients. In Fourier series
 9 encoding, such errors may cause the entire image boundary to be misplaced. However, wavelet
 10 based encoding enables the boundary to remain the same, except for the isolated region subject
 11 to the error, as illustrated in Figure 2(b). Accordingly, wavelet based encoding, more localized and
 12 more resilient to errors in transmission, is a preferred encoding method for describing boundaries.

13 Figures 6(a)-(c) illustrate an exemplary image encoding using a subband coding (SBC)
 14 technique. Region based subband coding (RBSBC) is described, for example, in “A Region-Based
 15 Subband Coding Scheme” by Casas, et. al., Signal Processing: Image Communication 10 (1997)
 16 173-200, which is incorporated herein by reference. Casas, et. al. disclose a region-based
 17 subband encoding scheme intended for efficient representation of the visual information contained
 18 in image regions of arbitrary shape. QMF filters are separately applied inside each region for the
 19 analysis and synthesis stages, using a signal-adaptive symmetric extension technique at region
 20 borders. The frequency coefficients corresponding to each region are identified over the various
 21 subbands of the decomposition, so that the encoding steps, namely, bit-allocation, quantization and
 22 entropy encoding, can be performed independently for each region.

23 An original image $I-V_0$ 310 is shown in Figure 6(a). $I-V_0$ 310 may be filtered and
 24 downsampled to generate subbands $I-V_{LL}$ 410, $I-W_{HL}$ 421, $I-W_{LH}$ 423, and $I-W_{HH}$ 425, as
 25 illustrated in Figure 6(b). The frequency representations are illustrated in Table 1. The subbands
 26 $I-V_{LL}$ 410, $I-W_{HL}$ 421, $I-W_{LH}$ 423, and $I-W_{HH}$ 425, drawn on a smaller (1/4 size) grid, may
 27 be combined to reconstruct $I-V_0$ 310, the original image.
 28
 29
 30

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29

Table 1

	Horizontal Frequencies	Vertical Frequencies
LL	Low Pass	Low Pass
LH	Low Pass	High Pass
HL	High Pass	Low Pass
HH	High Pass	High Pass

Referring to Figure 6(c), the subband $I-V_{ILL}$ 410 may be further filtered and downsampled to generate subbands $I-V_{2LL}$ 510, $I-W_{2HL}$ 521, $I-W_{2LH}$ 523, and $I-W_{2HH}$ 525. The subbands $I-V_{2LL}$ 510, $I-W_{2HL}$ 521, $I-W_{2LH}$ 523, and $I-W_{2HH}$ 525, drawn on a yet smaller (1/16 size) grid, may be combined to reconstruct $I-V_{ILL}$ 410.

Figures 7(a)-(d) illustrate an exemplary multi-resolution decomposition of an image and an associated boundary. Figure 7(a) illustrates an original image $I-V_0$ 310 composed of a set of regions, i.e., R_1 710, R_2 720, R_3 730, and R_4 740. The Regions are defined by a set of boundaries in $B-V_0$ 330, i.e., B_1 810, B_2 820, B_3 830, and B_4 840. Referring to Figure 7(b), the original image $I-V_0$ 310 may be filtered and downsampled to generate subbands $I-V_{ILL}$ 410, $I-W_{IHL}$ 421, $I-W_{ILH}$ 423, $I-W_{IHH}$ 425 for each of the regions within the image. $I-V_{ILL}$ 410 may be generated using low pass horizontal and low pass vertical (LL) frequency filters, $I-W_{IHL}$ 421 may be generated using high pass horizontal and low pass vertical (HL) frequency filters, $I-W_{ILH}$ 423 may be generated using low pass horizontal and low pass vertical (LH) frequency filters, and $I-W_{IHH}$ 425 may be generated using high pass horizontal and high pass vertical (HH) frequency filters. All four subbands have the same boundary resolution, i.e., $B-V_1$ 430.

Figure 7(c) illustrates a further decomposition, where the LL frequency subband $I-V_{ILL}$ 410 is further filtered and downsampled for each of the regions, generating smaller subbands $I-V_{2LL}$ 510, $I-W_{2HL}$ 521, $I-W_{2LH}$ 523, $I-W_{2HH}$ 525. The subbands $I-W_{IHL}$ 421, $I-W_{ILH}$ 423, $I-W_{IHH}$ 425 remain the same. The subbands $I-V_{2LL}$ 510, $I-W_{2HL}$ 521, $I-W_{2LH}$ 523, $I-W_{2HH}$ 525 have the same boundary resolution, i.e., $B-V_2$ 530, which has a lower resolution than $B-V_1$ 430.

Figure 7(d) illustrates another level of decomposition, where the LL frequency subband $I-V_{2LL}$ 510 is further filtered and downsampled for each of the regions, generating yet smaller

00879168-051304

1 subbands $I-V_{3LL}$ 610, $I-W_{3HL}$ 621, $I-W_{3LH}$ 623, $I-W_{3HH}$ 625. The subbands $I-W_{2HL}$ 521, $I-W_{2LH}$
 2 523, $I-W_{2HH}$ 525 remain the same as before. The subbands $I-V_{3LL}$ 610, $I-W_{3HL}$ 621, $I-W_{3LH}$ 623,
 3 $I-W_{3HH}$ 625 have the same boundary resolution, i.e., $B-V_3$ 630, which has a yet lower resolution
 4 than $B-V_2$ 530.

5 Decomposition may be performed as many times as necessary to encode the image and
 6 the corresponding boundary. Because downsampling is typically performed in both directions, one-
 7 fourth of the original data remains after each filtering. After filtering, a pyramid is generated with
 8 different frequency contents, i.e., resolutions. However, only four or five decompositions are
 9 typically performed. As a result of the multiple levels of decomposition, a complete image
 10 compression may be generated based on wavelet coefficients for the boundary and subband
 11 coefficients for the image.

12 In transmission, image and boundary information may be sent using joint source channel
 13 coding (JSCC) to protect the information against channel errors. JSCC describes techniques in
 14 which the compression function and the error control function in a communication system are
 15 combined in some way. For example, encoding of the boundary and image may be modified so
 16 that different resolutions may be protected unequally against errors in transmission channels, i.e.,
 17 the most important coefficients with respect to the human visual system (HVS) may be well
 18 protected, where the least important coefficients are less protected.

19 For example, when video signals are transmitted, image and corresponding boundary
 20 coefficients with the lowest resolution may be sent first. Next, image and boundary coefficients with
 21 a higher resolution may be transmitted, and so on. There are more data bits, i.e., energy, to be sent
 22 to encode a boundary in a subband with higher frequency. Image compression in source encoding
 23 is, in part, obtained by removing or coarsely encoding some of the coefficients in the higher
 24 frequency bands, i.e., quantization process, as the HVS typically may not notice the difference.
 25 Channel encoding assigns error protection to the image and boundary information, and JSCC
 26 organizes the source coded coefficients in the order of importance with respect to the HVS. JSCC
 27 then applies channel encoding techniques to the source coded coefficients, providing more
 28 protection to the more important, i.e., low frequency, coefficients and less protection to the less
 29 important, i.e., high frequency, coefficients.

09879158 061301
T09T90 89T4860

1 Figures 8(a)-(e) illustrate an exemplary process of progressive reconstruction of a
2 decomposed image and an associated boundary. First, referring to Figure 8(a), boundary
3 information with the lowest resolution, i.e., B-V₃ 630, may be transmitted. Then, image information
4 in the lowest subband I-V_{3LL} may be sent to fill the boundary. The lowest resolution boundary and
5 image information, which are well protected against noises and transmission errors, are good
6 representations of the original image at lower frequency. A receiver with low bandwidth may still
7 recover this basic approximation.

8 Referring to Figure 8(b), image information in the other three subbands I-W_{3HL} 621, I-
9 W_{3LH} 623, and I-W_{3HH} 625 may be sent. The four subbands I-V_{3LL} 610, I-W_{3HL} 621, I-W_{3LH}
10 623, and I-W_{3HH} 625 share the same boundary resolution, i.e., B-V₃ 630. This level of image
11 information is less protected against errors. A handheld wireless device, which operates in noisy
12 channels and has smaller displays, typically only receives this level of approximation. However, the
13 handheld wireless device may still render a video on the small display, which is a close
14 representation of the original boundary and image.

15 In Figure 8(c), the four subbands I-V_{3LL} 610, I-W_{3HL} 621, I-W_{3LH} 623, and I-W_{3HH} 625
16 may be combined to reconstruct the image information in I-V_{2LL} 510. Next, higher resolution
17 boundary information in B-W₃ 640 (not shown in Figure 8) may be sent. B-V₃ 630 and B-W₃ 640
18 may be combined to reconstruct B-V₂ 530, which has a higher resolution. Then, image information
19 in the other three subbands I-W_{2HL} 521, I-W_{2LH} 523, and I-W_{2HH} 525 may be transmitted. Again,
20 the subbands I-V_{2LL} 510, I-W_{2HL} 521, I-W_{2LH} 523, and I-W_{2HH} 525 share the same boundary
21 resolution, i.e., B-V₂ 530. The higher resolution boundary and image information are even less
22 protected against transmission errors.

23 Similarly, in Figure 8(d), the subbands I-V_{2LL} 510, I-W_{2HL} 521, I-W_{2LH} 523, and I-W_{2HH}
24 525 may be combined to reconstruct the image information in I-V_{1LL} 410. Next, higher resolution
25 boundary information in B-W₂ 540 (not shown in Figure 8) may be sent. B-V₂ 530 and B-W₂ 540
26 may be combined to reconstruct B-V₁ 430, which has yet a higher resolution. Then, image
27 information in the other three subbands I-W_{1HL} 421, I-W_{1LH} 423, and I-W_{1HH} 425 may be
28 transmitted. Once again, the subbands I-V_{1LL} 410, I-W_{1HL} 421, I-W_{1LH} 423, and I-W_{1HH} 425
29 share the same boundary resolution, i.e., B-V₁ 430. The boundary and image at this level of

09879158-061301

1 resolution are more vulnerable to errors in transmission, because they are not well protected in the
2 channel coding steps.

3 Lastly, referring to Figure 8(e), the subbands $I-V_{ILL}$ 410, $I-W_{IHL}$ 421, $I-W_{ILH}$ 423, and
4 $I-W_{IHH}$ 425 may be combined to reconstruct the original image $I-V_{OLL}$ 310. The original image $I-$
5 V_{OLL} 310 may be reproduced at a receiver. In this embodiment, the highest frequency coefficients
6 in $B-W_1$ 440 do not need to be transmitted. If a receiver, for example, a high definition television
7 or a desktop computer, is able to receive the levels of coefficients described above without error,
8 the receiver may receive a high resolution high quality video scene, or even recover the original
9 image, as shown in Figure 8(e).

10 Accordingly, multi-resolution encoding both in boundary and in image allows a system
11 designer to protect different sets of coefficients according to transmission channel's condition.
12 Different receivers, using different channels, may receive different amount of bits per second, i.e.,
13 bandwidth. Hand held low resolution devices may utilize only lower frequency resolution, which
14 is well protected. Other receivers, such as high definition televisions, use better channels with
15 higher frequency band and can receive better image quality.

16 The image encoding and the boundary encoding use the same subbands for convenience
17 purposes only. The two types of encoding may be performed separately and do not need to use
18 the same subbands. In addition, instead of using RBSBC for the image encoding, other encoding
19 methods may be used.

20 Figure 9 is a flow chart of the exemplary decomposition and reconstruction process
21 illustrated in Figures 7 and 8 using multi-resolution boundary encoding. An original image $I-V_0$ 310
22 may be divided into a plurality of regions, such as R_1 710, R_2 720, R_3 730, and R_4 740, step 910.
23 A plurality of boundaries, such as B_1 810, B_2 820, B_3 830, and B_4 840, may be detected, step
24 910. Next, each of the boundaries may be encoded by two periodic wavelet series, one for $x(t)$
25 and one for $y(t)$, so that each boundary may contain different sets of wavelet coefficients, step 912.
26 For example, for a three level decomposition, $B-V_0$ 330 may be composed of $2N$ wavelet
27 coefficients, N for $x(t)$ and N for $y(t)$, $B-V_1$ 430 may be composed of N wavelet coefficients, $N/2$
28 for $x(t)$ and $N/2$ for $y(t)$, $B-V_2$ 530 may be composed of $N/2$ wavelet coefficients, $N/4$ for $x(t)$
29 and $N/4$ for $y(t)$, and $B-V_3$ 630 may be composed of $N/4$ wavelet coefficients, $N/8$ for $x(t)$ and
30 $N/8$ for $y(t)$.

09579168-061301
110140-89162860

1 Next, using the boundaries with the highest resolution, i.e., B-V₀ 330, each of the regions
2 in the original image I-V₀ 310 may be decomposed into, for example, four subbands, using a
3 RBSBC scheme, step 914. The four subbands may be LL subband I-V_{ILL} 410, HL subband I-
4 W_{2HL} 521, LH subband I-W_{2LH}, and HH subband I-W_{2HH}, steps 916, 918, 920, and 922,
5 respectfully. In the next step, using lower resolution boundaries, each of the regions in the LL
6 subband may be successively decomposed into further four LL, LH, HL, and HH subbands, step
7 924. For example, using the boundary B-V₁ 430, each of the regions in the LL subband, i.e., I-
8 V_{ILL} 410, may be further decomposed into I-V_{2LL} 510, I-W_{2HL} 521, I-W_{2LH} 523, I-W_{2HH} 525.
9 In addition, using the boundary B-V₂ 530, each of the regions in the lower resolution LL subband,
10 i.e., I-V_{2LL} 510, may be further decomposed into I-V_{3LL} 610, I-W_{3HL} 621, I-W_{3LH} 623, I-W_{3HH}
11 625. Accordingly, after the successive decomposition, the following subbands are generated: one
12 subbands with the lowest image resolution I-V_{3LL} 610, three subbands I-W_{3HL} 621, I-W_{3LH} 623,
13 I-W_{3HH} 625, three subbands with higher image resolution I-W_{2HL} 521, I-W_{2LH} 523, I-W_{2HH} 525,
14 and three subbands with even higher image resolution.

15 During transmission, these boundary and image information may be sent using JSCC to
16 protect the information against channel errors. First, the lowest resolution boundary B-V₃ 630 may
17 be sent, step 926. This boundary information has the highest error protection. Next, the image
18 information in the lowest resolution subband I-V_{3LL} 610 may be sent, step 928. This image
19 information, again, has the highest error protection. In step 930, the image information in the lowest
20 resolution subbands I-W_{3HL} 621, I-W_{3LH} 623, I-W_{3HH} 625 may be transmitted. The subbands I-
21 V_{3LL} 610, I-W_{3HL} 621, I-W_{3LH} 623, and I-W_{3HH} 625 may be combined to reconstruct I-V_{2LL} 510
22 in a receiver, step 932.

23 In the next step, boundary information in a higher resolution may be successively
24 transmitted, step 934, together with the image information in a higher resolution HL, LH, and HH
25 subbands, step 936. Similarly, the subbands LL, HL, LH, and HH may be combined to
26 reconstruct image information in a higher resolution, until the original image I-V₀ 310 is
27 reconstructed, step 938. For example, boundary information in B-W₃ 640 may be sent, which,
28 by combining B-V₃ 630, may generate the boundary at resolution B-V₂ 530, which has high
29 protection. Then, the image information in I-W_{2HL} 521, I-W_{2LH} 523, I-W_{2HH} 525 may be sent,
30 which may be combined with I-V_{2LL} 510 to reconstruct I-V_{ILL} 410. Next, boundary information

1 in B-W₂ 540 may be sent, which may combine with B-V₂ 530, to generate the boundary at
2 resolution B-V₁ 430, which has medium protection. Finally, the image information in I-W_{IHL} 421,
3 I-W_{ILH} 423, I-W_{IHH} 425 may be sent, which may be combined with I-V_{ILL} 410 to reconstruct the
4 original image I-V₀ 310 in the receiver.

5 While the method for multi-resolution boundary encoding has been described in connection
6 with an exemplary embodiment, it will be understood that many modifications in light of these
7 teachings will be readily apparent to those skilled in the art, and this application is intended to cover
8 any variations thereof.

09879460 09879460